

NRP3 Rock Wool

3-Rib Roof Panel - Rock Wool · NRP3-RW

0.045

W/mK thermal conductivity

40 - 120

mm core thickness

1000


mm cover width

15.5

m maximum length

PRODUCT DESCRIPTION

NRP3 Rock Wool is the rock wool core version of the three-rib roof profile. The rib height is 37 mm. It is the profile chosen for buildings where the fire regulation requires class A2; the fire class is A2-s1-d0.



TECHNICAL PROPERTIES

Core material	Rock wool
Fire class	A2-s1-d0
Thermal conductivity	0.045 W/mK
Core thicknesses	40 mm · 50 mm · 60 mm · 70 mm · 80 mm · 100 mm · 120 mm
Facing options	Polyester · PVDF · Plastisol
Steel thicknesses	0.45 mm x 0.35 mm · 0.50 mm x 0.40 mm · 0.60 mm x 0.50 mm · 0.60 mm x 0.60 mm · 0.70 mm x 0.60 mm · 0.80 mm x 0.70 mm
Company certificates	ISO 9001 · ISO 14001 · ISO 45001 · TSE · YMB · CE

DIMENSIONS

DESIGN	COVER WIDTH	THICKNESS	MAXIMUM LENGTH
3 Hadveli	1000 mm	40 - 120 mm	15.5 m

FACING MATERIAL

EN 10143 · EN 10327

FACE	MATERIAL	THICKNESS	GRADE	GALVANISING
Outer	Steel sheet	0.45 - 0.80 mm	DX 51	100 - 110 gr/m ²
Inner	Steel sheet	0.35 - 0.70 mm	DX 51	100 - 110 gr/m ²

CORE MATERIAL

TS EN 14509 · TS EN 12667 · TS EN 13501-1

MATERIAL	DENSITY	THICKNESS	THERMAL CONDUCTIVITY	FIRE CLASS
Rock wool	90-130 kg/m ³ taşıyünü	40 - 120 mm	0.045 W/mK	A2-s1-d0

COATING

	REVERSE SIDE	PRIMER	TOP COAT	TOTAL FRONT
Polyester	7 microns	5 microns	20 microns	25 microns

THERMAL TRANSMITTANCE AND WEIGHT

THICKNESS	U (W/m ² K)	WEIGHT (kg/m ²)	THICKNESS	U (W/m ² K)	WEIGHT (kg/m ²)
40 mm	0.97	11.9	80 mm	0.52	15.9
50 mm	0.80	12.9	100 mm	0.42	17.9
60 mm	0.68	13.9	120 mm	0.36	19.9
70 mm	0.59	14.9			

The U-value is calculated for the panel section with the surface resistances of EN ISO 6946; the fastener correction depends on the project. The weight is the nominal value for a panel with 0.50/0.50 mm steel facings.

STANDARD COLOURS



3020

5010


7016

9002

9006

Custom colours are produced from the RAL range.

PANEL SECTION



JOINT DETAIL



FOR INFORMATION

www.nuhpanel.com.tr

+90 262 751 07 79

This technical data sheet has been prepared according to the current technical information and standards of Nuhpanel Yapı Elemanları Sanayi Ticaret A.Ş. (Gebze, Kocaeli). The right to make technical changes is reserved.



Product page