

GRP Panel - EPS

GRP Roof Panel - EPS · NRP5-CTP

0.038

W/mK thermal conductivity

30 - 120

mm core thickness

1000


mm cover width

15.5

m maximum length

PRODUCT DESCRIPTION

GRP Panel - EPS is a roof panel with an outer facing of glass-fibre reinforced polyester (GRP). The GRP facing is chosen for environments where pre-painted steel does not withstand chemical attack: manure, ammonia and washing chemicals.



TECHNICAL PROPERTIES

Core material	EPS
Fire class	-
Thermal conductivity	0.038 W/mK
Core thicknesses	30 mm · 40 mm · 50 mm · 60 mm · 70 mm · 80 mm · 100 mm · 120 mm
Facing options	Polyester · CTP
Steel thicknesses	0.45 mm x 0.35 mm · 0.50 mm x 0.40 mm · 0.60 mm x 0.50 mm · 0.60 mm x 0.60 mm · 0.70 mm x 0.60 mm · 0.80 mm x 0.70 mm
Company certificates	ISO 9001 · ISO 14001 · ISO 45001 · TSE · YMB · CE

DIMENSIONS

COVER WIDTH	THICKNESS	MAXIMUM LENGTH
1000 mm	30 - 120 mm	15.5 m

FACING MATERIAL

EN 10143 · EN 10327

FACE	MATERIAL	THICKNESS	GRADE	GALVANISING
Outer	Steel sheet	0.45 - 0.80 mm	DX 51	100 - 110 gr/m ²
Inner	Steel sheet	0.35 - 0.70 mm	DX 51	100 - 110 gr/m ²

CORE MATERIAL

TS EN 14509 · TS EN 12667 · TS EN 13501-1

MATERIAL	DENSITY	THICKNESS	THERMAL CONDUCTIVITY	FIRE CLASS
EPS	12-16 kg/m ³ EPS	30 - 120 mm	0.038 W/mK	-

COATING

	REVERSE SIDE	PRIMER	TOP COAT	TOTAL FRONT
Polyester	7 microns	5 microns	20 microns	25 microns

STANDARD COLOURS



3020

5010


7016

9002


9006

Custom colours are produced from the RAL range.

PANEL SECTION



JOINT DETAIL



FOR INFORMATION

www.nuhpanel.com.tr

+90 262 751 07 79

This technical data sheet has been prepared according to the current technical information and standards of Nuhpanel Yapı Elemanları Sanayi Ticaret A.Ş. (Gebze, Kocaeli). The right to make technical changes is reserved.



Product page